

provide designs which requires a relatively few design coordinates compared to the FIR time response samples for the waveform

provide design methodologies which can incorporate application metrics to improve the waveform performance

provide designs that allow the use of direct design methodologies that circumvent the need to solve a Wavelet iterated filter bank construction to obtain the waveforms thereby providing improved flexibility to meet the application goals

2. A means for the design of multi-resolution waveforms and filters in the frequency domain or equivalently the Fourier of the t-f space for waveform and filter applications, with properties which

provide a means for single design to be used for all of the waveforms at the multiple resolutions or frequency bands

provide a means for designs that require a relatively few design coordinates compared to the number of digital samples covered by the Wavelet

provide a means for the designs to include frequency and time application metrics to improve the waveform performance

provide a means to use direct design methodologies in the frequency-time domain for all of the waveforms and filters for the multiple frequency bands

3. A method for the design of multi-resolution waveforms which allows Fourier domain techniques to be used. Properties can include some or more of the listed properties in (1) and (2).

4. A method for the design of multi-resolution waveforms which can incorporate Fourier domain techniques into design methodologies which can include analytical and iterated filter bank construction design techniques.

5. A method for the analysis and design of multi-resolution waveforms using Fourier domain techniques which take advantage of the new invention disclosures on the characterization and design of multi-resolution waveforms in the Fourier domain.

6. A new formulation in (5) for multi-resolution waveform as a function of the dc multi-resolution waveform which adds the concept of a frequency index that allows the multi-resolution waveform to be placed arbitrarily throughout the t-f space thereby 1) avoiding the restrictions of the Wavelet iterated filter construction for tiling a t-f space, and 2) allowing the new multi-resolution waveforms to be used for multi-resolution communications and for bandwidth-on-demand communications application, in place of traditional Wavelets.

REFERENCES:

- [1] I. Daubechies, "Ten Lectures on Wavelets", Philadelphia:SIAM, 1992
- [2] Ronald R. Coifman, Yves Meyer, Victor Wickerhauser, "Wavelet analysis and signal processing", in "Wavelets and Their Applications", Jones & Bartlett Publishers, 1992
- [3] T. Blu, "A new design algorithm for two-band orthonormal rational filter banks and orthonormal rational Wavelets", IEEE Signal Processing, June 1998, pp. 1494-1504
- [4] M. Unser, P. Thevenaz, and A. Aldroubi, "Shift-orthogonal Wavelet bases", IEEE Signal Processing, July 1998, pp. 1827-1836
- [5] K.C. Ho and Y. T. Chan, "Optimum discrete Wavelet scaling and its application to delay and Doppler estimation", IEEE Signal Processing, Sept. 1998, pp. 2285-2290
- [6] Q. Pan, L. Zhang, G. Dai, and H. Zhang, "Two denoising methods by Wavelet transforms", IEEE Signal Processing, Dec. 1999, pp. 3401-3406
- [7] P.P. Vaidyanathan and T.Q. Nguyen, "Eigenvalues: A New Approach to Least-Squares FIR Filter Design and Applications Including Nyquist Filters", IEEE Trans. on Circuits and Systems, Vo. CAS-34, No. 1, Jan. 1987, pp 11-23
- [8] J.H. McClellan, T.W. Parks and L.R. Rabiner, "A Computer Program for Designing Optimum FIR Linear Phase Filters", IEEE Trans Audio Electroacoust. Vol. AU-21, Dec. 1973, pp. 506-526